

APPENDIX D
CIVIL AND STRUCTURAL DESIGN

This page intentionally left blank.

APPENDIX D

Civil and Structural Design

TABLE OF CONTENTS

1.0	GENERAL INFORMATION AND EXISTING CONDITIONS	1
1.1	GENERAL INFORMATION AND LAYOUT OF APPENDIX.....	1
1.2	EXISTING CONDITIONS	1
1.2.1	Original Condition - 1950s Design	2
1.2.2	Current Existing Condition (based on 2003 survey data)	15
1.2.3	Roads & Bridges	15
1.2.4	Existing Sumps and Pump Houses.....	21
1.2.5	Existing Utilities	22
2.0	THE CITY OF DALLAS' BALANCED VISION AND INTERIOR DRAINAGE PLANS	53
2.1	EVALUATION OF THE LOCAL SPONSOR PLAN WITH MDFP CRITERIA	53
2.1.1	Technically Sound	53
2.2	FLOOD RISK MANAGEMENT PLAN DEVELOPMENT	54
2.2.1	Alternatives Considered.....	54
2.2.2	Probable Failure Mode #2 – Overtopping and Subsequent Breach	55
2.2.3	Seepage at the Levee Foundation.....	70
2.2.4	Bridge Assumptions.....	78
2.2.5	Summary and Conclusions.....	90
2.3	FRM PLAN REFINEMENT	90
2.3.1	277K cfs Levee Raise	91
2.3.2	AT&SF Bridge Modification	97
2.3.3	Utilities.....	98
2.3.4	Bridge Work.....	98
2.3.5	Flood Risk Management Plan Conclusions	99
2.4	CITY PREFERENCE OF SLOPE FLATTENING.....	99
2.4.1	Modeling Process.....	99
2.4.2	Slope Stabilization under Bridges.....	105
2.4.3	Future Alternatives in Preconstruction Engineering and Design Phase.....	105
2.4.4	Utilities.....	106
2.4.5	Side Slope Flattening Conclusions	107
2.5	BALANCED VISION PLAN	107
2.5.1	Balanced Vision Plan Feature Categorization.....	108
2.5.2	River Relocation	110
2.5.3	Lakes	114
2.5.4	Cut-off Walls	122
2.5.5	Hardscape Features	123
2.5.6	Landscape Features.....	124
2.5.7	Corinth Wetlands	125

2.5.8	Utilities.....	125
2.5.9	Bridge Pier Modification	127
2.5.10	Proposed and Existing Feature Integration	129
2.5.11	Balanced Vision Plan Conclusions	130
2.6	INTERIOR DRAINAGE PLAN	131
2.6.1	Able Pump Station	131
2.6.2	Baker Pump Station	132
2.6.3	Charlie Pump Station	133
2.6.4	Delta Pump Station	134
2.6.5	Hampton Pump Station	134
2.6.6	Nobles Branch Sump	135
2.6.7	Pavaho Pump Station	136
2.6.8	Pavaho Sump Improvements	136
2.6.9	Trinity Portland Pump Station	136
2.6.10	Trinity Portland and Eagle Ford Sump Improvements	137
2.6.11	Outfall Structures	137
2.6.12	Sumps.....	138
2.6.13	Interior Drainage Plan Conclusions	138
2.7	PROJECT CONSTRUCTION PHASING.....	139
2.7.1	General Phasing Plan	139
2.7.2	Construction Phase 1 – Levee Work & AT&SF Bridge Modification	140
2.7.3	Construction Phase 2 – Interior Drainage Plan	140
2.7.4	Construction Phase 3, 4 and 5 – River Relocation.....	140
2.7.5	Construction Phase 6 – Lakes	141
2.7.6	Trinity Parkway Considerations.....	141
3.0	COMPREHENSIVE ANALYSIS.....	141
3.1	GOALS OF COMPREHENSIVE ANALYSIS	142
3.2	LOCAL FEATURES: SECTION 408 PROJECTS.....	142
3.2.1	Trinity Parkway	142
3.2.2	Pavaho Wetlands.....	147
3.2.3	Dallas Wave (Standing Wave).....	148
3.2.4	Santa Fe Trestle Trail.....	149
3.2.5	Horseshoe: IH-35E and IH-30	149
3.2.6	Sylvan Bridge.....	151
3.2.7	Jefferson Bridge.....	151
3.2.8	Continental Bridge	152
3.2.9	Dallas Water Utilities.....	152
3.3	IMPACTS OF CONSTRUCTION PHASING	152
3.4	OPERATION AND MAINTENANCE FOR THE BVP AND IDP.....	153
3.5	MECHANICAL AND ELECTRICAL DESIGN DISCUSSION	154
3.6	PROJECT RISKS.....	154
3.6.1	Overall Comprehensive Analysis Risks.....	154
3.6.2	Flood Risk Management Plan Risks	155
3.6.3	Balanced Vision Plan Risks	155
3.6.4	Quantities	155

3.7	CONCLUSIONS	156
3.7.1	Summary of Comprehensive Analysis.....	156
3.7.2	Final Considerations	157
4.0	MODIFIED DALLAS FLOODWAY PROJECT.....	157
4.1	PROJECT SCOPE.....	157
4.1.1	Flood Risk Management.....	159
4.1.2	Ecosystem Restoration.....	164
4.1.3	Borrow Sources.....	166
5.0	RECOMMENDED PLAN.....	168
6.0	REFERENCES.....	170
6.1	PLANS AND DESIGN DRAWINGS.....	170
6.2	REPORTS AND OTHER DOCUMENTATION	172

List of Figures

D-1	East Levee Profile I.....	3
D-2	East Levee Profile II	5
D-3	Elm Fork Levee Profile.....	7
D-4	West Levee Profile I	9
D-5	West Levee Profile II.....	11
D-6	West Fork Levee Profile	13
D-7	Bridges Crossing the Dallas Floodway	19
D-8	Key for Detailed Figures Depicting Utilities Located Within and Adjacent to the Dallas Floodway Levee System.....	23
D-9	Utilities Details: Map 1	25
D-10	Utilities Details: Map 2.....	27
D-11	Utilities Details: Map 3.....	29
D-12	Utilities Details: Map 4.....	31
D-13	Utilities Details: Map 5.....	33
D-14	Utilities Details: Map 6.....	35
D-15	Utilities Details: Map 7.....	37
D-16	Utilities Details: Map 8.....	39
D-17	Utilities Details: Map 9.....	41
D-18	Utilities Details: Map 10.....	43
D-19	Utilities Details: Map 11	45
D-20	Utilities Details: Map 12.....	47
D-21	Utilities Details: Map 13.....	49
D-22	Utilities Details: Map 14.....	51
D-23	Levee Raise Template 4H:1V Side Slopes	56
D-24	Initial Access Road Cross Section	56
D-25	Approximate Locations of Borrow Pits	63

D-26	Existing Levee Armoring Template.....	66
D-27	Cut-Off Wall with No Clay Cap	71
D-28	Seepage Blanket.....	73
D-29	Cut-Off Wall with Clay Cap.....	75
D-30	Levee Cap under Bridges.....	83
D-31	Levee Cap Detail.....	85
D-32	Levee Cap Under Bridges Work Phases	87
D-33	Revised Proposed Access Road Cross Section.....	92
D-34	Typical Side-Slope Flattening Template.....	100
D-35	Example Condition Side-Slope Flattening Template.....	100
D-36	Scarification Estimation Process.....	103
D-37	Flood Separation Wall and East Levee Interface.....	145
D-38	3H:1V Levee Raise Template.....	161
D-39	New Crushed Limestone Access Road Template.....	161
D-40	4H:1V Typical Levee Side Slope Flattening Template	162

List of Tables

D-1	Bridge Low Beam and Deck Elevation Relative to 277K cfs Flow with and without AT&SF Railroad Bridge Removal.....	16
D-2	Initial Quantities for 260K, 277K, and 302K cfs Flows	57
D-3	Quantities for 260K, 265K, 269K, 273K, and 277K cfs Flows	58
D-4	Quantities for 277K and 289K cfs Flows with 3H:1V Side Slopes	59
D-5	Levee and River Stationing for Raising East and West Levees.....	61
D-6	Borrow Pit Materials.....	66
D-7	Quantities for Armoring All Reaches of Levees.....	67
D-8	Levee and River Stationing for Armoring East and West Levees	68
D-9	Quantities for Armoring up to Water Surface Elevations.....	69
D-10	Quantities Seepage Mitigation Cut-Off Walls	77
D-11	Bridge Crossings Impacted at 277K cfs Flow Water Surface Elevation	79
D-12	Additional Bridge Crossings Impacted at 289K cfs Flow Water Surface Elevation	80
D-13	Additional Bridge Crossings Impacted at 302K cfs Flow Water Surface Elevation	80
D-14	Flow Velocity and Duration of Contact at Bridge Crossings Impacted at 277K cfs Flow Water Surface Elevation.....	89
D-15	Scaled 277K Levee Raise Quantities from Table D-4.....	93
D-16	Revised Levee Raise Lengths from Initial NED Plan Formulation.....	94
D-17	Comprehensive Analysis 277K cfs Levee Raise Quantities	95
D-18	Quantities for Levee Raise under Bridges Scheduled for Replacement	96
D-19	FRM Plan Refinement of Levee Raise Borrow Pits	97
D-20	AT&SF Bridge Earthen Berm Removal	98
D-21	Levee Side Slope Flattening Quantities	103
D-22	Levee Side Slope Flattening Borrow Pits	104
D-23	Required Utility Relocations for 4H:1V Side Slope Flattening.....	107
D-24	Lake Descriptions	115

D-25	Bridge Pier Modification Summary	128
D-26	Construction Phases	139
D-27	BVP and IDP and the Modified Dallas Floodway Project.....	158
D-28	Stationing of East and West Levee Reaches to be Raised	160
D-29	Utility Relocations for Side Slope Flattening	162
D-30	Utility Relocations for River Relocation	165
D-31	BVP Rough Quantities.....	166
D-32	Plans and Design Drawings Utilized in Comprehensive Analysis	170
D-33	Reports and Other Documentation Referenced in Comprehensive Analysis	172

List of Civil & Structural Plans

G-191	Project Location Map
C-201 TO C-204	East Levee Profile with Existing Levee Height and Levee Raise to 277K Water Surface
C-205 TO C-209	West Levee Profile with Existing Levee Height and Levee Raise to 277K Water Surface
C-210 TO C-212	Trinity River Relocation Profile
C-213	Oxbow Profile
C-301 TO C-306	East Levee Existing and New Cross Sections with Borings
CD101	AT&SF Bridge Removal Schematic Plan
CG100	Overall FRM and Side Slope Flattening Plan
CG101 TO CG107	FRM and Side Slope Flattening Grading with location of Borrow Pits Plans
CS100	Overall Site Key Plan
CS101 TO CS108	BVP with Parkway and IDP Site Plans
CS109 TO CS118	BVP without Parkway and IDP Site Plans
CU101	Central Wastewater Treatment Plant Effluent 60" Pipe Plan
C-501	Levee Raise and Slope Flattening Template
C-502	FRM Borrow Pit Typical Cross Section
C-503	Typical Concrete Rip-Rap Under Bridges
C-504 TO C-505	Typical Bridge Pier Modification Cross Sections
C-506 TO C-507	City of Dallas Cut-Off Wall Typical Details

This page intentionally left blank.

1.0 GENERAL INFORMATION AND EXISTING CONDITIONS

1.1 GENERAL INFORMATION AND LAYOUT OF APPENDIX

The purpose of this appendix is to provide feasibility level engineering information in support plan formulation for the Water Resources Development Act (WRDA) 2007 Section 5141 of the City's Balanced Vision Plan (BVP) and Interior Drainage Plan (IDP) as well as several local features in a "Comprehensive Analysis." The focus of this appendix is on existing and future-without project conditions, plan formulation and evaluation, the findings of the Comprehensive Analysis, and the final determination of the Modified Dallas Floodway Project (to implement under Section 5141 of WRDA 2007). Civil drawings are provided at the end of this appendix.

An evaluation was completed to determine whether the various projects in the BVP and IDP were technically sound. The first evaluation was conducted on the City of Dallas' BVP and IDP Plans with respect to the technical soundness of each feature and its compatibility with neighboring features within the Dallas Floodway, Section 2. This evaluation included a National Economic Development (NED) Analysis of various probable failure modes to determine a flood risk management (FRM) plan, then a study of the various BVP features, and finally a discussion on the proposed IDP features. Each feature is discussed in detail within the report and is followed by a determination of technical soundness. See Section 2.1 for the definition of technical soundness used within the context of this report.

Following an evaluation of the City's BVP and IDP, a Comprehensive Analysis was conducted to determine the compatibility of the BVP, IDP and local features within the Dallas Floodway Levee System, see Section 3. The currently known set of local features was determined based on information provided in design submittals to USACE. A key local feature evaluated was the Trinity Parkway. Two designs were developed for the BVP regarding the Trinity Parkway; one assuming the Trinity Parkway in the future condition, and one without the Trinity Parkway in the future condition. These two designs were the plans evaluated in the Environmental Impact Statement (EIS) completed for the BVP and IDP. The Trinity Parkway runs along the riverside toe of the East Levee and directly impacts a large portion of the BVP and IDP. Reviews pertaining to a Section 408 are included after discussions of each local feature in Section 3.0. It is important to note, the Comprehensive Analysis modeled features from a hydrologic and hydraulic perspective collectively and not on an individual basis. Civil and Structural design reviewed the projects from a technical perspective on an individual basis, and will continue to analyze at an individual level under the Corps Section 408 review process and future Planning Engineering and Design (PED) phase of the Recommended Plan for the MDFP.

During the evaluation of the City's BVP and IDP and the Comprehensive Analysis, a Recommended Plan for the Modified Dallas Floodway Project (MDFP) was determined based on two project objectives: FRM and environmental restoration. Recreation features of the BVP were found to be beyond the USACE mission for recreation; therefore, construction of recreation features was not included in the MDFP. A subset of the City's BVP and IDP was recommended for inclusion into the federal plan as authorized by WRDA 2007. The MDFP, and its features are described in Section 4. The features included in the MDFP satisfy the project objectives and will be cost-shared between the Federal Government and the local sponsor, the City of Dallas.

1.2 EXISTING CONDITIONS

The existing Dallas Floodway Levee System, authorized in 1945, extends along the Trinity River upstream from the Atchison, Topeka, and Santa Fe (AT&SF) Railroad Bridge at Trinity River Mile (RM)

497.37, to the confluence of the West and Elm Forks at RM 505.50, thence upstream along the West Fork for approximately 2.2 miles and upstream along the Elm Fork approximately 4 miles. Of the 22.6 miles of levees within this reach, the East Levee is 11.7 miles in length and the West Levee is 10.9 miles in length. The existing Dallas Floodway Levee System includes the levees, river channel, 6 pumping plants, 18 sump storage ponds, 7 pressure storm sewers, and 3 gravity sluices. Several different surveys have been used in the preparation of this report. A topographic survey (with two foot interval contours) from 1991 covers the entire Floodway area. A one-foot contour interval topographic survey that was performed in 2003 covers the downstream portion of the levees and documents the levee modifications performed by the City of Dallas in the early 1990s. A bathymetric survey of the Trinity River channel was performed in 2004. A survey of the low beam elevations on many of the bridges that cross the Floodway was performed in 2003. Older surveys were based on a datum of NAVD 1929 and more recent surveys are based on a datum of NAVD 1988. However, elevation differences between these two datum are on the order of a few hundredths of a foot within the project area and are considered insignificant relative to the accuracy of the surveys themselves. Therefore, differences in datum are not considered to be a concern with regard to the accuracy of the results of this study. The most current survey of the Dallas Floodway was a LIDAR survey completed by HNTB in 2009. This information is available but not discussed in this report at this time. The purpose of maintaining the old survey information for continued evaluation is to create and maintain an established baseline across all disciplines. An updated survey with more detailed information on the interior of the Dallas Floodway System will be created and utilized before future stages of design.

Construction of the existing Dallas Floodway Levee System was completed in 1959. The distance between the levees varies between approximately 2,000 feet to 2,600 feet. The levees are approximately 30 feet high with slopes that vary. The levee system will be discussed providing information for the current existing condition, the 1950s design and as-built condition of the levees. The stationing discussed in the narrative and shown on figures or maps translate forward from the initial 1950s design of both levees. See Figures D-1 through D-8 for aerial photography maps with levee and river stationing displayed.

1.2.1 Original Condition - 1950s Design


1.2.1.1 Slopes

According to the as-built plans, the original construction of the East Levee consisted of a 3:1 (horizontal: vertical) slope for the river side of the levees. The protected or land side of the levees were constructed of mainly of 3.5:1 slopes. The only exception found was that the slopes of the East Levee land side were varied slightly to 3:1 at station 305+00 and also from station 387+00 to station 405+00. As-built plans for the West Levee show that the levee was constructed with a 3:1 slope on both the land side and the river side. There was only one location where the slope was slightly lessened to a 3.5:1 slope. This was shown on the landside of the West Levee near station 322+11.

1.2.1.2 Levee Height

The as-built (design grade) elevations for both the East and West Levees (including the Elm and West Fork Levees) are shown as compared to existing elevations and various flows' water surface elevations in Figures D-1 through D-6. These profiles were determined using HEC-RAS models. Their creation as well as the correlation between flow volume and water surface elevation is discussed further in the Hydraulics and Hydrology Appendix (Appendix A of this report) in Section 6. Sections 2.2.2 and 2.2.3 describe the further utilization of Figures D-1 through D-6.

Dallas Floodway ATSF Bridge Removed Trinity River Main Stem



Legend

- WS 302k
- WS 289k
- Future SPF 277k
- Current SPF 269k
- WS 260k
- Levee D.G.
- East Levee Crest



US Army Corps of Engineers
Fort Worth District

Symbol	Description	Tracking No.	Action	Date

Designed by:	Date:	Rev.
Dwn by:	Scale:	
Reviewed by:	Contr. No.:	
Submitted by:	Plot date:	Plot scale:
DAVID C. BROWN, P.E.	8/1/2013	
CHIEF, CIVIL SECTION		

U.S. ARMY ENGINEER DISTRICT,
CORPS OF ENGINEERS
FORT WORTH, TEXAS

ENGINEERING/
CONSTRUCTION DIVISION
DESIGN BRANCH

DALLAS FLOODWAY LEVEE STUDY
DALLAS, TEXAS

FIGURE D-1
EAST LEVEE PROFILE I


Sheet reference number:

This page intentionally left blank.

P:\Trinity_Rvr_Ban\Dallas_Flewy\Civil_Engineering\NRM_PLANNING_REAL_EST\STATE_OF_LEVEE_RE-G.bs.dgn

REFERENCE FILES:
DF-RMC-C:\gmd\LEAST2-FIC.dgn

Dallas Floodway ATSF Bridge Removed Trinity River Main Stem



Legend

- WS 302k
- WS 289k
- Future SPF 277k
- Current SPF 269k
- WS 260k
- Levee D.G.
- East Levee Crest



Symbol	Description	Tracking No.	Action	Date

Designed by:	Date:	Rev.
Dwn by:	Sol No.	
Reviewed by:	Contr. No.	
Submitted by:		
DAVID C. BROWN, P.E.		
CHIEF, CIVIL SECTION		
	Plot date: 8/1/2013	
	Plot scale:	

U.S. ARMY ENGINEER DISTRICT,
CORPS OF ENGINEERS
FORT WORTH, TEXAS

ENGINEERING/
CONSTRUCTION DIVISION
DESIGN BRANCH

DALLAS FLOODWAY LEVEE STUDY
DALLAS, TEXAS

FIGURE D-2
EAST LEVEE PROFILE II


Sheet reference number:

Contr. No.

This page intentionally left blank.

P:\Trinity_Rvr_Ban\Dallas_Flowy\Civil_Engineering\NRM_PLANS\DF_REAL_EST\STATE_OF_LEVEE_RE-G.bs.dgn
 P:\Trinity_Rvr_Ban\Dallas_Flowy\Civil_Engineering\NRM_PLANS\DF_REAL_EST\STATE_OF_LEVEE_RE-G.bs.dgn
 DF-D-3.dgn
 4/18/2013 8:29:38 AM

Dallas Floodway ATSF Bridge Removed Elm Fork Trinity River



Legend

- WS 302k
- WS 289k
- Future SPF 277k
- Current SPF 269k
- WS 260k
- Levee D.G.
- East Levee Crest



Symbol	Description	Frequency No.	Action	Date

Designed by:	Date:	Rev.
Dwn by:	Scale:	
Reviewed by:	Contr. No.	
Submitted by:	Per name:	
DAVID C. BROWN, P.E.	4/18/2013	
CHIEF, CIVIL SECTION	Port scale:	

U.S. ARMY ENGINEER DISTRICT,
 CORPS OF ENGINEERS
 FORT WORTH, TEXAS

ENGINEERING/
 CONSTRUCTION DIVISION
 DESIGN BRANCH

DALLAS FLOODWAY LEVEE STUDY
 DALLAS, TEXAS

FIGURE D-3
 ELM FORK LEVEE PROFILE

Sheet reference number:

Contr. No.


This page intentionally left blank.

This page intentionally left blank.

This page intentionally left blank.

P:\Trinity_Rvr_Ban\Dallas_Flowy\Civil\Engineering\NRM\PLAN\DF_REAL\ESTATE\DF_LEVEE_RE-G-bs.dgn
 4/18/2013 8:38:43 AM
 DF-D-6.dgn

Dallas Floodway ATSF Bridge Removed West Fork Trinity River



Legend

- WS 302k
- WS 289k
- Future SPF 277k
- Current SPF 269k
- WS 260k
- Levee D.G.
- West Levee Crest



US Army Corps of Engineers
 Fort Worth District

Symbol	Description	Tracking No.	Action	Date

U.S. ARMY ENGINEER DISTRICT, CORPS OF ENGINEERS FORT WORTH, TEXAS	Designed by: D. DANG	Date:	Rev.
	Dwn by: C. CHIN	Soil No.	
ENGINEERING/ CONSTRUCTION DIVISION DESIGN BRANCH	Reviewed by: J. MCKENZIE, P.E.	Contr. No.	
	Submitted by: DAVID C. BROWN, P.E. CHIEF, CIVIL SECTION	Plot date: 4/18/2013	Plot scale:

DALLAS FLOODWAY LEVEE STUDY
 DALLAS, TEXAS

FIGURE D-6
 WEST FORK LEVEE PROFILE

Sheet reference number:

This page intentionally left blank.

1.2.2 Current Existing Condition (based on 2003 survey data)

The top of the existing levees are approximately 16 feet wide and are topped with an access road made of crushed limestone. Interior drainage on the land side of the levees is accommodated by a system of sumps and pump stations. Within this study area, numerous highway and railroad bridges cross the Floodway. A 1,334 linear foot concrete floodwall completes the downstream end of the East Levee and is located just upstream of DART Railway Bridge. This floodwall provides a tie-back to high ground for the existing earthen levee. The floodwall originally had four stop-log structures, two of which have been removed and replaced with earthen fill.

1.2.2.1 Slopes

For both the East and West Levee located upstream of the Inwood Road/N. Hampton Road Bridge (station 292+00 for the East Levee and station 252+00 for the West Levee), the slopes vary slightly from 3:1 to 3.5:1. From the Inwood Road/N Hampton Road Bridge downstream to the Sylvan Road Bridge (station 225+00 for the East Levee and station 185+00 for the West Levee), the slopes are indicated to vary between 3:1 to 3.4:1. From the Sylvan Bridge downstream to the IH-30 Bridge (station 120+00 for the East Levee and station 105+00 for the West Levee), the slopes begin to lessen. Slopes start around 3.3:1 vertical and vary to nearly 4:1 as the levees approach IH-30. The slope of the East Levee slightly steepens to 3.7:1 beginning approximately 620-feet north of the IH-30 Bridge. Between the IH-30 Bridge and the Jefferson Boulevard (station 96+00 for the east levee and station 66+00 for the West Levee) bridge, the East Levee begins with a slope of 3:1. The slope gently tapers to a 4:1 but then steepens again to nearly 3:1 as it approaches the Houston and Jefferson bridges. These two bridges are located near station 100+00 of the East Levee and station 68+77 for the West Levee. The West Levee starts out at a steeper 2.8:1, flattens out to a 4:1 slope, and then steepens again to 3.5:1 as it approaches the Jefferson Blvd Bridge. Continuing from the Jefferson Blvd Bridge, both levees have slopes that vary from 3.7:1 to 4:1. Throughout the Floodway, the surface data indicated that steeper slopes near 2.5:1 exist along the maintenance access roads traversing the levee slopes.

1.2.3 Roads & Bridges


Beginning at the downstream end of the Floodway and preceding upstream, the bridges shown in Figure D-7 cross the Floodway and/or Levees. The low beam and deck elevations are shown in comparison to the 277, 000 cfs flow both with and without the AT&SF Railroad Bridge removal in Table D-1. The partial removal of the AT&SF Railroad Bridge on the far downstream end of the Floodway is one of the FRM options being looked at to reduce the overall risk and water surface elevation of the Floodway. See Sections 2.2.1.2 and 2.3.2 for more information. Bridges highlighted in green are in stages of being replaced by other entities and the shown information is based on the existing bridge. The completion of the proposed project features is not necessarily predicated on the construction and completion of the new bridges. The gray row in the East Levee bridge descriptions designates the beginning of the Elm Fork Levee. The gray row in the West Levee bridge descriptions indicates the start of the West Fork Levee.

Table D-1. Bridge Low Beam and Deck Elevation Relative to 277K cfs Flow with and without AT&SF Railroad Bridge Removal

East Levee								
Bridge Name	277K Water Surface Elev. (feet)	277K WSE (With AT&SF Bridge Removal) (feet)	Low Beam Elev. (feet)	Bridge Deck Elev. (feet)	Low Beam Freeboard (feet)	Low Beam Freeboard (With AT&SF Removal) (feet)	Bridge Deck Freeboard (feet)	Bridge Deck Freeboard (With AT&SF Removal) (feet)
Dallas Area Rapid Transit (DART)	425.00	424.35	431.00		6.00	6.65		
Corinth	425.45	424.46	424.00	429.00	-1.45	-0.46	3.55	4.54
IH-35 (Northbound) (R.L. Thornton Freeway)	426.38	425.43	423.00	428.20	-3.38	-2.43	1.82	2.77
IH-35 (Southbound) (R.L. Thornton Freeway)	426.63	425.70	424.11	428.30	-2.52	-1.59	1.67	2.60
Jefferson	426.93	426.04	430.95	436.20	4.02	4.91	9.27	10.16
Houston	427.30	426.41	430.10	438.70	2.80	3.69	11.40	12.29
IH-30 Exit	428.27	427.47	426.54	431.50	-1.73	-0.93	3.23	4.03
IH-30 (Eastbound)	428.37	427.58	427.29	432.70	-1.08	-0.29	4.33	5.12
IH-30 (Westbound)	428.37	427.58	428.40	433.10	0.03	0.82	4.73	5.52
IH-30 Entrance	428.37	427.58	427.50	432.30	-0.87	-0.08	3.93	4.72
Commerce	429.03	428.28	428.54	432.20	-0.49	0.26	3.17	3.92
U.P. R.R.	429.60	428.96	428.61	436.00	-0.99	-0.35	6.40	7.04
Margaret Hunt Hill	429.87	429.25	436.27		6.40	7.02		
Continental	430.04	429.43	429.20	434.30	-0.84	-0.23	4.26	4.87
Sylvan (old)	431.51	431.00	427.52		-3.99	-3.48		
Hampton/Inwood	432.88	432.44	438.84	445.35	5.96	6.40	12.47	12.91
Westmoreland	433.98	433.59	435.71	442.00	1.73	2.12	8.02	8.41
Shady Grove/ E. Irving Blvd	435.98	435.67	436.94	441.00	0.96	1.27	5.02	5.33
SH-356	436.03	435.73	434.31	438.90	-1.72	-1.42	2.87	3.17
DART Trinity Rail Express (C.R.I.& PAC.) RR (old bridge)	436.09	435.78	440.68	444.50	4.59	4.90	8.41	8.72
DART Trinity Rail Express C.R.I.& PAC. RR (new bridge)	436.09	435.78	438.44		2.35	2.66		
SH-183	437.04	436.77	437.67	442.00	0.63	0.90	4.96	5.23

West Levee								
Bridge Name	277K Water Surface Elev. (feet)	277K WSE (With AT&SF Bridge Removal) (feet)	Low Beam Elev. (feet)	Bridge Deck Elev. (feet)	Low Beam Freeboard (feet)	Low Beam Freeboard (With AT&SF Removal) (feet)	Bridge Deck Freeboard (feet)	Bridge Deck Freeboard (With AT&SF Removal) (feet)
Corinth	425.45	424.46	424.37		-1.08	-0.09		
IH-35 (Northbound) (R.L. Thornton Freeway)	426.38	425.43	424.13		-2.25	-1.30		
IH-35 (Southbound) (R.L. Thornton Freeway)	426.63	425.70	425.01		-1.62	-0.69		
Jefferson	426.93	426.04	431.42	437.30	4.49	5.38	10.37	11.26
Zang Blvd	427.04	426.15	444.91	450.00	17.87	18.76	22.96	23.85
Houston	427.30	426.41	418.50	424.47	-8.80	-7.91	-2.83	-1.94
IH-30 (Eastbound)	428.37	427.58	428.89	433.20	0.52	1.31	4.83	5.62
IH-30 (Westbound)	428.37	427.58	428.89	433.00	0.52	1.31	4.63	5.42
Commerce	429.03	428.28	430.15	432.50	1.12	1.87	3.47	4.22
U.P. R.R.	429.60	428.96	430.22	435.50	0.62	1.26	5.90	6.54
Margaret Hunt Hill	429.87	429.25	434.22		4.35	4.97		
Continental	430.04	429.43	430.00	434.30	-0.04	0.57	4.26	4.87
Sylvan (old)	431.51	430.86	429.52		-1.99	-1.34		
Hampton/Inwood	432.88	432.44	439.23	445.21	6.35	6.79	12.33	12.77
Westmoreland	433.98	433.59	436.04	441.50	2.06	2.45	7.52	7.91
Loop 12	438.15	437.85	441.22	448.00	3.07	3.37	9.85	10.15
Singleton	438.74	438.46	440.00	444.10	1.26	1.54	5.36	5.64



This page intentionally left blank.



**Figure D-7
Bridges Crossing the Dallas Floodway**

LEGEND

-  Bridges
-  Pumping Plant
-  Dallas Floodway Levee System
Levee
-  Freeway
-  Study Area
-  Dallas Floodway
-  Surface Water



Sources: City of Dallas 2008a, NCTCOG 2008

This page intentionally left blank.

1.2.3.1 Roads and Bridges Assumptions and Preliminary Design Criteria

Water surface elevations are based on the current HEC-RAS steady state model for the 277,000 cubic feet per second flow through the Floodway. The water surface elevations are shown with and without the FRM measure of removing the AT&SF Bridge (See Section 2.2.1.2 and Section 2.3.2). The AT&SF Bridge, as described in Sections 2.2.1.2 and 2.3.2, is one of the potential FRM solutions analyzed in this report. Low beam freeboard refers to the amount of distance between the low beam (the lowest chord elevation of the bridge) and the corresponding water surface elevation. Bridge deck freeboard refers to the difference in elevation between the water surface elevation and the elevation of the bridge deck used by vehicular traffic. A negative number (in red) indicates that the low beam or bridge deck is below the projected water surface elevation. A bridge element with a negative freeboard would be submerged and subject to additional stresses at the specified water surface elevation. At the downstream end of the Levee System, the East Levee turns and extends northeast, parallel to and beneath the DART Bridge for approximately 1,100 feet. The DART Bridge is on a grade which ascends toward the east, so most of the 1,100 feet of levee under the bridge has more clearance than implied by the elevation listed in the table. The IH-35 Roadway crossing of the Elm Fork Levee at the far upstream end of the levee is not displayed in the above table. The roadway is supported by an earthen berm that extends out from the levee towards the river. There is clearance between the water surface elevation at this location and the top of the earthen embankment. Similar circumstances to this occur at the far upstream end of the West Fork Levee with regards to the IH-30 Roadway. The rows highlighted in green are roadways and bridges that are scheduled to be rebuilt at a higher elevation and are not considered issues in further discussion of bridge crossings.

1.2.4 Existing Sumps and Pump Houses

The existing East and West Levees prevent the local storm water runoff from draining directly to the river. The storm water runoff collects in low lying areas on the land side of the levees until it can be pumped into the river, drain through pressure storm sewers, or drain through gravity sluices. A system of sumps areas, pressure storm sewers, and pump houses has been constructed to accommodate the interior drainage. The City of Dallas Trinity River Flood Control District operates and maintains the system, which requires a substantial staff of personnel.

The City utilizes a sophisticated Supervisory Control and Data Acquisition system (SCADA) to help operate and control the pumping plants. The following list summarizes the pump house facilities. Refer to Section 2.6 of this appendix for a more detailed description of the existing interior drainage system. The attached plan set depicts the proposed interior drainage facilities. The IDP proposals are described in Section 2.6.

Able Pump Station

This plant, located on the East Levee downstream of IH-30, contains two pump houses. The old pump house has two 10,000 gallons per minute (gpm) pumps with 85 horsepower (hp) motors each. This facility includes two 4' x 4' sluice structures with manually operated sluice gates and flap gates.

Baker Pump Station

This plant, located on the East Levee between Inwood Avenue and Sylvan Avenue, contains four 54,000 gpm pumps. The facility includes four 6' diameter gravity sluice pipes with four 72 inch diameter hand operated sluice gates and flap gates.

Charlie Pump Station

This plant, located on the West Levee downstream of IH-30, contains two 30,000 gpm pumps with 125 hp motors each. This facility also includes two 4' x 4' gravity sluices with two manually operated sluice gates and flap gates.

Delta Pump Station

This plant, located on the West Levee upstream of Inwood Avenue, contains two 30,000 gpm pumps with 125 hp motors each. This facility also includes two 4' x 4' gravity sluices with two manually operated sluice gates and flap gates.

Pavaho Pump Station

This plant, located on the West Levee upstream of Continental Street, contains two 30,000 gpm pumps with 250 hp motors each. This facility also includes two 6' x 8' gravity sluices with two motor operated sluice gates and flap gates.

Hampton Pump Station

This plant, located on the East Levee upstream of Hampton Avenue, contains four 50,000 gpm pumps with 600 hp motors each. This facility also includes four 42" outside diameter discharge lines.

1.2.5 Existing Utilities

Numerous utilities intersect with the existing Dallas Floodway Levee System. Refer to Figures D-8 to D-22 for depictions of the existing utilities within and adjacent to the Dallas Floodway Levee System. The problems associated with these crossing configurations and the potential solutions are discussed in the following sections of the report. Utilities affected are divided up by the specific feature that requires the modification of the utility.

Utilities are discussed on a per project basis. Therefore, utilities affected by a certain feature are discussed in that section. The same utility may be discussed in multiple sections of the report based on how multiple projects affect the same utility. Cost for utility modification is assigned on a per project basis based on which project affects the utility. Different costs for the same utility may be attributed to multiple projects because of future project phasing.

One utility that is currently under construction in the Dallas Floodway Levee System is the East Bank-West Bank Interceptor. This interceptor is a sanitary sewer line that runs perpendicular to the levees and crosses the Dallas Floodway just downstream from the proposed IH-35E. This sanitary sewer line will become an existing condition prior to much of the construction in the Dallas Floodway. The sanitary sewer line includes a new 78" and 96" line ending at a 40' diameter terminus near the West Levee. This terminus is referred to as a siphon in some documentation. See Geotechnical Appendix B for more information about this utility.






Figure D-8
Key for Detailed Figures Depicting Utilities Located
within and Adjacent to the Dallas Floodway Levee System

LEGEND

-  Dallas Floodway Levee System Levee Crest
-  Dallas Floodway Levee System Levee
-  Study Area
-  Index

Note: Detailed figures are presented at the end of the utilities section



Source: USACE 2011






This page intentionally left blank.



Figure D-9
Utilities Details: Map 1

LEGEND

Utility Lines		Dallas Floodway Levee System
Electrical		Levee Crest
Electrical Substation		Manhole
Communication		Exterior Light
Wastewater		Power Pole
Sewer		Transmission Tower
Natural Gas		Key
Petroleum		CRI&P Chicago, Rock Island and Pacific Railroad
Water		Ex. Existing
Abandoned Oil and Gas		HP High Pressure
		IH Interstate Highway
		IP Intermediate Pressure
		KV Kilovolt
		OH Overhead
		SH State Highway
		SFB Suspended From Bridge
		UG Underground
		WW Wastewater



Source: USACE 2011



This page intentionally left blank.

This page intentionally left blank.







Figure D-11
Utilities Details: Map 3

LEGEND

Utility Lines	Dallas Floodway Levee System
Electrical	Levee Crest
Electrical Substation	Manhole
Communication	Exterior Light
Wastewater	Power Pole
Sewer	Transmission Tower
Natural Gas	Key
Petroleum	CRI&P Chicago, Rock Island and Pacific Railroad
Water	Ex. Existing
Abandoned Oil and Gas	HP High Pressure
	IH Interstate Highway
	IP Intermediate Pressure
	KV Kilovolt
	OH Overhead
	SH State Highway
	SFB Suspended From Bridge
	UG Underground
	WW Wastewater



Source: USACE 2011






This page intentionally left blank.



Figure D-12
Utilities Details: Map 4

LEGEND

Utility Lines	Dallas Floodway Levee System
Electrical	Levee Crest
Electrical Substation	Manhole
Communication	Exterior Light
Wastewater	Power Pole
Sewer	Transmission Tower
Natural Gas	Key
Petroleum	CRI&P Chicago, Rock Island and Pacific Railroad
Water	Ex. Existing
Abandoned Oil and Gas	HP High Pressure
	IH Interstate Highway
	IP Intermediate Pressure
	KV Kilovolt
	OH Overhead
	SH State Highway
	SFB Suspended From Bridge
	UG Underground
	WW Wastewater



Source: USACE 2011



This page intentionally left blank.






Figure D-13
Utilities Details: Map 5

LEGEND

Utility Lines		Dallas Floodway Levee System
Electrical	Levee Crest	Manhole
Electrical Substation	Exterior Light	Power Pole
Communication	Transmission Tower	
Wastewater		
Sewer		
Natural Gas		
Petroleum		
Water		
Abandoned Oil and Gas		

Key

CRI&P	Chicago, Rock Island and Pacific Railroad
Ex.	Existing
HP	High Pressure
IH	Interstate Highway
IP	Intermediate Pressure
KV	Kilovolt
OH	Overhead
SH	State Highway
SFB	Suspended From Bridge
UG	Underground
WW	Wastewater



Source: USACE 2011






This page intentionally left blank.



Figure D-14
Utilities Details: Map 6

LEGEND

Utility Lines		Dallas Floodway Levee System
Electrical	Levee Crest	Manhole
Electrical Substation	Exterior Light	Power Pole
Communication	Transmission Tower	
Wastewater		
Sewer	Key	
Natural Gas	CRI&P Chicago, Rock Island and Pacific Railroad	
Petroleum	Ex Existing	
Water	HP High Pressure	
Abandoned Oil and Gas	IH Interstate Highway	
	IP Intermediate Pressure	
	KV Kilovolt	
	OH Overhead	
	SH State Highway	
	SFB Suspended From Bridge	
	UG Underground	
	WW Wastewater	



Source: USACE 2011






This page intentionally left blank.



Figure D-15
Utilities Details: Map 7

LEGEND

Utility Lines	Dallas Floodway Levee System
Electrical	Levee Crest
Electrical Substation	Manhole
Communication	Exterior Light
Wastewater	Power Pole
Sewer	Transmission Tower
Natural Gas	Key
Petroleum	CRI&P Chicago, Rock Island and Pacific Railroad
Water	Ex. Existing
Abandoned Oil and Gas	HP High Pressure
	IH Interstate Highway
	IP Intermediate Pressure
	KV Kilovolt
	OH Overhead
	SH State Highway
	SFB Suspended From Bridge
	UG Underground
	WW Wastewater



Source: USACE 2011



This page intentionally left blank.